

POE++



- Cat6 U/UTP PVC Network Patch Leads
- Flush Moulded Strain Relief boot
- Stranded Copper 7/0.2 24AWG
- Constructed with RJ45 Plugs
- 10/100/1000 BASE-T Gigabit Ethernet
- Operating Temperature Range: -20°C to 60°C
- Storage Temperature Range: -20°C to 60°C
- Bulk Pack Contains Either 100 or 50 Leads Depending On Length - Individual Patch Leads In ONE Overall Bag

Product Features

- Constructed with high quality RJ45 plugs and UL approved stranded copper Cat6 cable
- 10/100/1000 BASE-T Gigabit Ethernet
- 24AWG Stranded Copper cable used
- 143c Pantone Number

Product Description

Cablenet Category6 PVC U/UTP Bulk network leads are manufactured, tested and verified to the ISO 11801 Class E and ANSI/EIA/TIA standards for enhanced performance

They are constructed with RJ45 plugs and high quality stranded Cat6 UL approved cable

Other lengths and colours are available in the bulk pack options, please contact our sales team for more information

Part Code Description

60-5003B	0.3m Cat6 RJ45 Yellow U/UTP PVC 24AWG Flush Moulded Booted Patch Lead (PK 100)
60-5005B	0.5m Cat6 RJ45 Yellow U/UTP PVC 24AWG Flush Moulded Booted Patch Lead (PK 100)
60-5010B	1m Cat6 RJ45 Yellow U/UTP PVC 24AWG Flush Moulded Booted Patch Lead (PK 100)
60-5015B	1.5m Cat6 RJ45 Yellow U/UTP PVC 24AWG Flush Moulded Booted Patch Lead (PK 100)
60-5020B	2m Cat6 RJ45 Yellow U/UTP PVC 24AWG Flush Moulded Booted Patch Lead (PK 100)
60-5050B	5m Cat6 RJ45 Yellow U/UTP PVC 24AWG Flush Moulded Booted Patch Lead (PK 50)

****PLEASE NOTE THESE NETWORK PATCH LEADS ARE NOT INDIVIDUALLY LABELLED****

**** Full Gold is a TM of Cablenet Trading Ltd for our RJ45 connectors that comply to IEE802.3bt/ISO IEC PoE Standards with 50-micron connectors**