



- Cat6 U/UTP PVC Network Patch Leads
- Flush Moulded Strain Relief Boot
- Stranded Copper 7/0.2 24AWG
- PoE++ Industry Rated Full Gold IEC 60603-7 RJ45 Cat6 Connectors
- 10/100/1000 BASE-T Gigabit Ethernet
- Operating Temperature Range: -20°C to 60°C
- Storage Temperature Range Range: -20°C to 60°C
- Available in 10 Different Colours

Product Features

- PoE++ Industry Rated Full Gold IEC 60603-7 RJ45 Cat6 Connectors
- 10/100/1000 BASE-T Gigabit Ethernet
- 24AWG Stranded Copper cable used
- 3415c Pantone Number

Product Description

Cablenet Category6 PVC U/UTP leads are manufactured, tested and verified to the ISO 11801 Class E and ANSI/EIA/TIA standards for enhanced performance

They are constructed with IEC 60603-7 RJ45 connectors that use "Full Gold" RJ45 and a high quality PoE++ certified cable.

These are available in 14 different lengths and manufactured in 10 colours

Part Code	Description
60-3003	0.3m Cat6 RJ45 Green U/UTP PVC 24AWG Flush Moulded Booted Patch Lead
60-3005	0.5m Cat6 RJ45 Green U/UTP PVC 24AWG Flush Moulded Booted Patch Lead
60-3010	1m Cat6 RJ45 Green U/UTP PVC 24AWG Flush Moulded Booted Patch Lead
60-3015	1.5m Cat6 RJ45 Green U/UTP PVC 24AWG Flush Moulded Booted Patch Lead
60-3020	2m Cat6 RJ45 Green U/UTP PVC 24AWG Flush Moulded Booted Patch Lead
60-3025	2.5m Cat6 RJ45 Green U/UTP PVC 24AWG Flush Moulded Booted Patch Lead
60-3030	3m Cat6 RJ45 Green U/UTP PVC 24AWG Flush Moulded Booted Patch Lead
60-3040	4m Cat6 RJ45 Green U/UTP PVC 24AWG Flush Moulded Booted Patch Lead
60-3050	5m Cat6 RJ45 Green U/UTP PVC 24AWG Flush Moulded Booted Patch Lead
60-3080	8m Cat6 RJ45 Green U/UTP PVC 24AWG Flush Moulded Booted Patch Lead
60-3100	10m Cat6 RJ45 Green U/UTP PVC 24AWG Flush Moulded Booted Patch Lead
60-3150	15m Cat6 RJ45 Green U/UTP PVC 24AWG Flush Moulded Booted Patch Lead
60-3200	20m Cat6 RJ45 Green U/UTP PVC 24AWG Flush Moulded Booted Patch Lead
60-3300	30m Cat6 RJ45 Green U/UTP PVC 24AWG Flush Moulded Booted Patch Lead

****Full Gold is a TM of Cablenet Trading Ltd for our RJ45 connectors that comply to IEE802.3bt/ISO IEC PoE Standards with 50-micron connectors**