



- Cat6a 10G U/FTP Slimline Network Patch Lead
- Flush Moulded Strain Relief Snagless Boot
- PoE++ Industry Rated Full Gold IEC 60603-7 RJ45 Cat6a Connectors
- 10/100/1000 Base-T Ethernet
- Supports up to 10G Base-T Ethernet
- Stranded Copper 30AWG
- Operating Temperature Range: -30 °C to 80 °C
- Nominal Outside Diameter 4.8mm (35% thinner than standard)

Product Features

- PoE++ Industry Rated Full Gold IEC 60603-7 RJ45 Cat6a Connectors
- 17% thinner than standard Cat6a Patch Lead - 4.8mm for Slimline compared to 5.8mm for Standard
- 30AWG Stranded Copper Cable

Product Description

Cablenet Category6a LSOH Slimline U/FTP leads are manufactured, tested and verified to the ISO 11801 Class Ea and ANSI/EIA/TIA standards for enhanced performance.

They are constructed with IEC 60603-7 RJ45 connectors that use "Full Gold" RJ45 and a high quality PoE++ certified cable.

These are also available in 10 different lengths and manufactured in 9 colours.

Part Code Description

Part Code	Description
SL65-6002	0.25m Cat6a RJ45 Black U/FTP LSOH 30AWG Slim Snagless Booted Patch Lead
SL65-6003	0.3m Cat6a RJ45 Black U/FTP LSOH 30AWG Slim Snagless Booted Patch Lead
SL65-6005	0.5m Cat6a RJ45 Black U/FTP LSOH 30AWG Slim Snagless Booted Patch Lead
SL65-6010	1m Cat6a RJ45 Black U/FTP LSOH 30AWG Slim Snagless Booted Patch Lead
SL65-6015	1.5m Cat6a RJ45 Black U/FTP LSOH 30AWG Slim Snagless Booted Patch Lead
SL65-6020	2m Cat6a RJ45 Black U/FTP LSOH 30AWG Slim Snagless Booted Patch Lead
SL65-6025	2.5m Cat6a RJ45 Black U/FTP LSOH 30AWG Slim Snagless Booted Patch Lead
SL65-6030	3m Cat6a RJ45 Black U/FTP LSOH 30AWG Slim Snagless Booted Patch Lead
SL65-6040	4m Cat6a RJ45 Black U/FTP LSOH 30AWG Slim Snagless Booted Patch Lead
SL65-6050	5m Cat6a RJ45 Black U/FTP LSOH 30AWG Slim Snagless Booted Patch Lead
SL65-6070	7m Cat6a RJ45 Black U/FTP LSOH 30AWG Slim Snagless Booted Patch Lead
SL65-6100	10m Cat6a RJ45 Black U/FTP LSOH 30AWG Slim Snagless Booted Patch Lead

****Full Gold is a TM of Cablenet Trading Ltd for our RJ45 connectors that comply to IEEE802.3bt/ISO IEC PoE Standards with 50-micron gold connectors**